

PRESSURE ABF FOAM FIRE EXTINGUISHER

TRISN2 Bio+ • TRISN3 Bio+ • TRISN6 Bio+ • TRISN9 Bio+



Type	Capacity kg / ltr.	Rating (LE*)	Operating temp °C	Discharge time ca. s	Throw range ca. m	Dimensions H x B x T ca. mm	Cylinder Ø mm	Weight ca. kg	Approval No. DIN EN 3	MED
TRISN2 Bio+	2	8A / 34B / 5F (2 / 2 / -)	0 – + 60	13	4 - 6	410 x 185 x 120	110	3,9	SP 86/13	-
TRISN3 Bio+	3	8A / 55B / 25F (2 / 3 / -)	0 – + 60	13	4 - 6	470 x 185 x 135	125	6,1	SP 87/13	-
TRISN6 Bio+	6	21A / 144B / 40F (6 / 9 / -)	0 – + 60	30	4 - 6	525 x 270 x 170	160	9,9	SP 88/13	●
TRISN9 Bio+	9	27A / 183B / 40F (9 / 10 / -)	0 – + 60	42	4 - 6	575 x 270 x 195	185	14,5	SP 89/13	-

Ratings / fire objects according to DIN EN 3, Extinguishing agent units according to ASR A2.2.

*If fire extinguishers are intended for both fire classes A+B vorgesehen, the lower LE value applies for the calculation. Technical changes & errors excepted.

2014/90/EU

All Ratings in accordance with DIN EN 3.

We reserve the right to change specifications without prior notice. 01/2021

MED

